

## H60130 Series

H60130 series standard precise slip ring , integrated structure design, with through hole 60mm , OD130mm , suitable for rotating application which requires a through hole <=60mm ( remark: if need a hole <60mm, can add a inner bushing)

### Part No. description


H60130 - Lower circuits no. - Signal circuits no. - Product grade

H:through hole slip ring  
60130:ID 60mm, OD 130mm

Example:  
0610:6 circuits,10A per circuit  
1220:2circuits,10A per circuit

Example:  
C: standard level  
D:Industrial level  
H:High quality level

Example:  
06S:6circuits signal (0~2A)  
12S:12circuits signal (0~2A)



### Standard Model List

H60130 series model list							
art no.	Circuit		Length L(mm)	art no.	Circuit		Length L(mm)
	10A	Signal or 5A			10A	Signal or 5A	
H60130-02S	0	2	36	H60130-36S	0	36	172
H60130-0210	2	0	36	H60130-0610-30S	6	30	172
H60130-03S	0	3	40	H60130-1210-S24	12	24	172
H60130-0310	3	0	40	H60130-3610	36	0	172
H60130-06S	0	6	52	H60130-42S	0	42	196
H60130-0210-04S	2	4	52	H60130-0610-36S	6	36	196
H60130-0410-02S	4	2	52	H60130-1210-30S	12	30	196
H60130-0610	6	0	52	H60130-4210	42	0	196
H60130-12S	0	12	76	H60130-48S	0	48	220
H60130-0210-10S	2	10	76	H60130-0610-42S	6	42	220
H60130-0310-09S	3	9	76	H60130-1210-36S	12	36	220
H60130-0610-06S	6	6	76	H60130-1810-30S	18	30	220
H60130-0810-04S	8	4	76	H60130-2410-24S	24	24	220
H60130-1010-02S	10	2	76	H60130-4810	48	0	220
H60130-1210	12	0	76	H60130-60S	0	60	268
H60130-18S	0	18	100	H60130-0610-54S	6	54	268
H60130-0210-16S	2	16	100	H60130-0910-51S	9	51	268
H60130-0410-14S	4	14	100	H60130-1210-48S	12	48	268
H60130-0610-12S	6	12	100	H60130-2410-36S	24	36	268
H60130-0810-10S	8	10	100	H60130-72S	0	72	316

Par no.	10A	Signal or 5A	Leng h L(mm)	Part no.	10A	Signal or 5A	Leng h L(mm)
H60130-1010-08S	10	8	100	H60130-1210-60S	12	60	316
H60130-1210-06S	12	6	100	H60130-2410-48S	24	48	316
H60130-1410-04S	14	4	100	H60130-3610-36S	36	36	316
H60130-1610-02S	16	2	100	H60130-84S	0	84	364
H60130-24S	0	24	124	H60130-1210-72S	12	72	364
H60130-0410-20S	4	20	124	H60130-2410-60S	24	60	364
H60130-0610-18S	6	18	124	H60130-3610-48S	36	48	364
H60130-1210-12S	12	12	124	H60130-96S	0	96	412
H60130-1810-06S	18	6	124	H60130-1210-84S	12	84	412
H60130-2410	24	0	124	H60130-2410-72S	24	72	412
H60130-30S	0	30	148	H60130-3610-60S	36	60	412
H60130-0610-24S	6	24	148	H60130-4210-54S	42	54	412
H60130-1210-18S	12	18	148	H60130-108S	0	108	460
H60130-1810-12S	18	12	148	H60130-1210-96S	12	96	460
H60130-2410-06S	24	6	148	H60130-2410-84S	24	84	460
H60130-3010	30	0	148	H60130-3610-72S	36	72	460

Remark: Circuits can be combined in parallel for bigger current, N circuits of 10A or N\*10A, such as 2 circuits of 10A in parallel for 20A use. 10A circuits No. and signal circuits (5A) No. can be customized based on standard products, please inquire for details.

### Technical Specification

Mechanical		Electrical		
Spec	Data	Spec	Data	
Working life	pls refer to product grade table		Power	Signal
Rotating speed	pls refer to product grade table	Rated voltage	0~690VAC/VDC	0~440VAC/VDC
Working temp.	-30°C~80°C	Insulation resistance	≥1000mΩ/500VDC	≥1000mΩ/500VDC
Work humidity	0~85% RH	Lead wire spec	AWG17# Silver-plated enameled	AWG22# Silver-plated enameled
Contact material	pls refer to product grade table	Lead wire length	standard 300mm (can be customized)	
Housing material	AL alloy	Dielectric strength	800VAC@50Hz, 60s	
Torque	0.1N.m (+0.03N.m/6circuits)	Electrical noise	<0.01Ω	
IP grade	IP51			

### Product Grade Table

Grade code	Max rotating speed	Working life	Contact material
C: standard	400RPM	20millions revolutions	precious metal
D: industrial	800RPM	60millions revolutions	precious metal
H: high quality	1200RPM	150millions revolutions	gold alloy

### Color code of Lead Wire

ring#	1	2	3	4	5	6	7	8	9	10	11	12
color	BLK	BRN	RED	ORG	YEL	GRN	BLU	PUR	GRY	WHT	PINK	LGT BLU
ring#	13	14	15	16	17	18	19	20	21	22	23	24
color	WHT/BLK	WHT/BRN	WHT/RED	WHT/ORG	WHT/YEL	WHT/GRN	WHT/BLU	WHT/PUR	WHT/GRY	BLK/RED	BLK/BRN	Transparent

Remark: "1" : the first wire from rotor side, H60130-06S wire color sequence: BLK/BRN/RED/ORG/WHT/GRN, 24 color wires as one group, if more than 24 wires, repeat as sequence, use number to denote each group 1#, 2#...