

Input voltage	Output voltage	Output current	Output power	Efficiency	Size
28-50V DC	12V DC	30 Amps	360 Watts	95%	100*80*39mm



Features


- Design meeting RoHS / CE
- High efficiency: 95% (@ 36V input)
- Non-isolated between input and output
- Internal capacitor: NCC & NICHICON (high reliability)
- 100% full load burn-in test
- Over load, Over temperature and Over voltage protections
- Waterproof level IP68
- 1 Year warranty

Applications

- Trucks
- Forklifts
- Buses
- Logging Vehicles
- Electromotor
- Telecommunications
- Boat & Yacht
- LED Marketplaces and so on..

Model naming method

WG-36S1230



Specifications

Model	WG-36S1230		
Input	Rated voltage	V	36
	Voltage range	V	28-50
	Efficiency (type)	%	95 @ 36V input
	Positive cable (red)	AWG	14 @ 15cm length
	Negative cable (black)	AWG	14 @ 15cm length
Output	Voltage	V	12
	Max. rated current	A	30
	Max. rated power	W	360
	Voltage regulation	%	±1
	Load regulation	%	2
	No load loss	mA	60 @ 36V input
	Ripple & noise	mV	160-210 (full load)
	Positive cable (white)	AWG	12 @ 15cm length
	Negative cable (black)	AWG	12 @ 15cm length
Environment	Working temperature	°c	-40 ~ +80
	Working humidity	RH	10% ~ 90%
	Storage temperature	°c	-40 ~ +100
Function	Short circuit protection		YES
	Over current protection	A	@ 35~40A
	Waterproof		IP68
	Over temperature protection		YES
	Over voltage protection		YES
Mechanical	Weight	g	480
	Size	mm	100*80*39
Other	Cooling		Free air convection
	Packaging		White box

Dimension

100 x 80 x 39 mm

