

Input voltage	Output voltage	Output current	Output power	Efficiency	Size
35-60V DC	24V DC	15 Amps	360 Watts	97%	100*80*39mm




### Features

- Design meeting RoHS / CE
- High efficiency: 97% ( @ 48V input )
- Non-isolated between input and output
- Internal capacitor: NCC & NICHICON (high reliability)
- 100% full load burn-in test
- Over load, Over temperature and Over voltage protections
- Waterproof level IP68
- 1 Year warranty

### Applications

- Trucks
- Forklifts
- Buses
- Logging Vehicles
- Electromotor
- Telecommunications
- Boat & Yacht
- LED Marketplaces and so on..

### Model naming method



### Specifications

Model	WG-48S2415		
Input	Rated voltage	V	48
	Voltage range	V	35-60
	Efficiency (type)	%	97 @ 48V input
	Positive cable (red)	AWG	14 @ 15cm length
	Negative cable (black)	AWG	14 @ 15cm length
Output	Voltage	V	24
	Max. rated current	A	15
	Max. rated power	W	360
	Voltage regulation	%	±1
	Load regulation	%	2
	No load loss	mA	70 @ 48V input
	Ripple & noise	mV	240-250 (full load)
	Positive cable (white)	AWG	14 @ 15cm length
	Negative cable (black)	AWG	14 @ 15cm length
Environment	Working temperature	°C	-40 ~ +80
	Working humidity	RH	10% ~ 90%
	Storage temperature	°C	-40 ~ +100
Function	Short circuit protection		YES
	Over current protection	A	@ 23~25A
	Waterproof		IP68
	Over temperature protection		YES
	Over voltage protection		YES
Mechanical	Weight	g	480
	Size	mm	100*80*39
Other	Cooling		Free air convection
	Packaging		White box

### Dimension

100 x 80 x 39 mm

