

Input voltage	Output voltage	Output current	Output power	Efficiency	Size
8-36V DC	12V DC	25 Amps	300 Watts	95%	100*80*39mm



Features


- Design meeting RoHS / CE
- High efficiency: 95% (@ 12V input)
- Non-isolated between input and output
- Internal capacitor: NCC & NICHICON (high reliability)
- 100% full load burn-in test
- Short circuit, Over load, Over temperature protections
- Waterproof level IP68
- 1 Year warranty

Applications

- Trucks
- Forklifts
- Buses
- Logging Vehicles
- Electromotor
- Telecommunications
- Boat & Yacht
- LED Marketplaces and so on..

Model naming method

WG8-36S1225



Specifications

Model	WG8-36S1225		
Input	Rated voltage	V	12/24
	Voltage range	V	8-36
	Efficiency (type)	%	95% @ 12V input
	Positive cable (red)	AWG	10 @ 16cm length
	Negative cable (black)	AWG	10 @ 16cm length
Output	Voltage	V	12
	Max. rated current	A	25
	Max. rated power	W	300
	Voltage regulation	%	±1
	Load regulation	%	2
	No load loss	mA	60
	Ripple & noise	mV	170
	Positive cable (white)	AWG	12 @ 16cm length
	Negative cable (black)	AWG	12 @ 16cm length
Environment	Working temperature	°c	-35 ~ +80
	Working humidity	RH	10% ~ 90%
	Storage temperature	°c	-50 ~ +125
Function	Short circuit protection		YES
	Over load protection	A	YES, @ 27-28
	Waterproof		IP68
	Over temperature protection		YES
	Over voltage protection		YES
Mechanical	Weight	g	480
	Size	mm	100*80*39
Other	Cooling		Free air convection
	Packaging		White box

Dimension

