

Input voltage	Output voltage	Output current	Output power	Efficiency	Size
9-36V DC	24V DC	10 Amps	240 Watts	97%	100*80*39mm



Features


- Design meeting RoHS / CE
- High efficiency: 97% (@ 24V input)
- Non-isolated between input and output
- Internal capacitor: NCC & NICHICON (high reliability)
- 100% full load burn-in test
- Short circuit, Over load, Over temperature protections
- Waterproof level IP68
- 1 Year warranty

Applications

- Trucks
- Forklifts
- Buses
- Logging Vehicles
- Electromotor
- Telecommunications
- Boat & Yacht
- LED Marketplaces and so on..

Model naming method

WG9-36S2410



Specifications

Model	WG9-36S2410		
Input	Rated voltage	V	12/24
	Voltage range	V	9-36
	Efficiency (type)	%	97% @ 24V input
	Positive cable (red)	AWG	12 @ 16.5cm length
	Negative cable (black)	AWG	12 @ 16.5cm length
Output	Voltage	V	24
	Max. rated current	A	10
	Max. rated power	W	240
	Voltage regulation	%	±1
	Load regulation	%	2
	No load current	mA	73 (@24Vin)
	Ripple & noise	mV	258 (@24Vin)
	Positive cable (yellow)	AWG	14 @ 16.5cm length
	Negative cable (black)	AWG	14 @ 16.5cm length
Environment	Working temperature	°c	-35 ~ +65
	Working humidity	RH	10% ~ 90%
	Storage temperature	°c	-40 ~ +100
Function	Short circuit protection		YES
	Over current protection	A	@ 12~13
	Waterproof		IP68
	Over temperature protection		YES
	Over voltage protection		YES
Mechanical	Weight	g	470
	Size	mm	100*80*39
Other	Cooling		Free air convection
	Packaging		White box

Dimension

